


Double Coated Tape A-7720D

Technical Data Sheet

General Description Soken Tape A-7720D is a reworkable double coated PET film core adhesive tape with high performance acrylic adhesives that provides good initial tack and offers high ultimate adhesion to a wide variety of surfaces.

Product Construction



Tape Thickness: 0.125 mm

Characteristics

- High adhesion with good balance of adhesive strength, holding power and tack. Also good balance of removability and resistance
- Could be removed without tearing the tape
- Excellent performance under a wide range of temperature
- Excellent resistance against repellent force and durability for ageing
- High adhesion to metal, glass, plastics and PU foam and other various surfaces

Applications

- General industrial use such as automobile, electronic product, and OA equipment etc.
- Household use, stationery, posters, etc.
- Attachment to various surfaces like metal, plastics, PE foam, urethane foam

Properties

Item	Value	Test Procedures
Peel Strength (N/m)	880	180 degree peel at 300mm/min, 23 °C 65%RH, to test plate, 20min conditioning time
Holding Power (mm)	0.3	1kg weight held for 1 hour to SUS with 20×20mm overlap area at 40°C, 20min conditioning time
Ball tack	22	23 °C 65%RH, according to J Dow method

Shelf Life

Six months from the date of receipt by customer when stored in the original packaging at 5~30°C and up to 50% Relative Humidity.

DISCLAIMER: The above figures are taken from experiments conducted under standard conditions at Soken Chemical Asia Co.,Ltd. They are not meant to be guaranteed values, to serve as reference only. Thorough evaluation of the actual application of Soken Tape must be conducted before use.

Authorized Distributor in Thailand:

MaterialOne (Thailand) Limited 568/4 Soi Lat Phrao 112 (Aumsomboon), Lat Phrao Rd., Phlappla, Wang Thonglang Bangkok 10310 Tel.02-026-3363 Fax.02-539-6319 E-mail: cs@materialone.co.th